

Your Energy Saving Expert



## PowerFusion Series

### X250KT DG Hybrid Energy Storage System

250kVA / 153.6kWh

Makes Diesel Generator Set Energy Saving and Efficient.



Meet the needs of high-load or high-impact loads in industrial applications, such as construction, manufacturing, and mining. Widely used for temporary power consumption and emergency power supply.

#### All-In-One

Integrated Battery + SEMS + SPCS

8 Sets Parallel  
Up to 2MW / 1228.8kWh

250 kW  
High Output

#### Rapid Deployment

Support lifting and forklift transportation



#### AC-Coupled Power System

Diesel GEN/PV System/Grid

#### Remote Monitoring & Management

via App and Web



#### Plug & Play

No installation required



[sales@roypow.com](mailto:sales@roypow.com)

[www.roypow.com](http://www.roypow.com)

## Technical Specifications

### Model

X250KT-U/A

### AC Output Data (On-grid Mode)

Rated Power	150 kW
Max. Overload Capacity	250 kVA @210s, R Load
Rated Voltage	480 V (±10%)
Rated Current	180 A
Grid Frequency	60 Hz
AC Connection	3 W + N + PE
THDI	≤ 3%
Power Factor	-1 ~ +1

### AC Output Data (Off-grid Mode)

Rated Power	150 kW
Max. Overload Capacity	250 kVA @210s, R Load
Rated Voltage / Frequency	480 V / 60 Hz
THDV (Linear Load)	≤3%

### Battery Data

Battery Chemistry	LiFePO4
Nominal Energy	153.6 kWh
Working Voltage Range	600 V ~ 876 V
Nominal Charging Current	100 A
Nominal Discharging Current	200 A
Max. Discharging Current	300 A
DOD	90%

### Compatible Diesel Generator

Rated Power	≤400 kVA
Rated Voltage	480 V
Rated Frequency	60 Hz

### General

Parallel Capable	Yes ( Up to 8)
EMS	SEMS3000 12 inch LCD Touch Panel
Ingress Rating	NEMA 3R
Topology	Transformer
Working Temperature	-4 ~ 122°F (-20 ~ 50°C)
Storage Temperature	-40 ~ 149°F (-40 ~ 65°C)
Relative Humidity	5 ~ 95% (No condensing)
System Noise	<65 dB
Cooling	Intelligent temperature control (Battery room) Air cooling (Inverter room)
Fire Suppression System	Included
Altitude	2,000m
Dimensions, LxWxH	90.6 x 68.9 x 94.5 inch (2,300 x 1,750 x 2,400 mm)
Weight	11243.5 lbs (5,100 kg)

Note: All data are based on ROYPOW standard test procedures, actual performance may vary according to local conditions.